



# PRODUCT DATA SHEET



## Decarock Natural Stone Panel System

<b>1. About the product</b>	<p><b>Material -</b></p> <p>Decarock Natural Stone Cladding consisting of pieces of natural stone lightly held in place with a small amount of epoxy resin to a fibreglass mesh backing to create an interlocking Z shape for fitting to a suitable substrate with a suitable adhesive.</p> <p>Decarock Natural Stone Veneer consists of pieces of natural stone held together in an interlocking Z shape with a waterproof adhesive to allow for fitting to a suitable substrate with a suitable adhesive.</p>
<b>1.2 Uses</b>	Internal/External wall facade
<b>2.1 Fixing</b>	Decarock Natural Stone Cladding should be fixed with either Decarock Natural Stone Cladding Adhesive or Ardex X7G+ according to the manufacturer's instructions. Decarock Natural Stone Veneer should be fixed with either Decarock Natural Stone Cladding Adhesive or Ardex X7G+ according to the manufacturer's instructions. It can also be fixed in small areas with Sika Maxtack Super Charged adhesive according to the manufacturer's instructions.
<b>2.2 Supporting Structure</b>	Decarock Natural Stone Cladding cannot be fixed directly to timber, plasterboard or painted surfaces. Standard blockwork or shuttered concrete walls are suitable. For timber frame applications a suitable render board (Renderpro by Magply or similar) should be fixed before and the loading checked with an engineer prior to application.

<b>3.1 Weight</b>	For Cladding allow for 65kg per square metre. For Veneer allow for 45kg per square metre.
<b>4.1 Composition of Cladding: (*All finishes except Black Limestone)</b>	<p>Standard panel: 4no 550x150mm panels packed in a cardboard box</p> <p>Long Corner: 4no 550x150mm panels with 1x finished end packed in a cardboard box</p> <p>Short Corner: 8no approx. 300x150mm panels with 1x finished end packed in a cardboard box</p> <p>*Black Limestone: as above except the panels are 200mm high not 150mm.</p> <p>All finishes are approximately 35mm thick.</p>
<b>4.2. Composition of Veneer:</b>	<p><b>Black Slate &amp; Antique Slate:</b></p> <p>7no panels (550x150mm) packed in cardboard box @ 0.64sqm. 7no long corners &amp; 7no short corners (sizes vary) packed in a cardboard box @ 0.64sqm.</p> <p><b>Desert Gold:</b></p> <p>6no panels (550x150mm) packed in a cardboard box @ 0.54sqm. 6no long corners &amp; 6no short corners (sizes vary) packed in a cardboard box @ 0.54sqm.</p> <p>All finishes are approximately 20mm thick</p>
<b>5. Samples</b>	Samples are available on request to ensure contract agreement.
<b>6. Supplier Reference:</b>	Rowebb Ltd. 33-53 Charles Street, Glasgow G21 2PR Tel: 0141 548 6010 E-mail: rowebb@rowebb.com

